



D'cover-plus®

Corte transpirable
Breathable upper
Tige respirante



D'dry®

Forro transpirable
Breathable lining
Doublure respirante



Suela antibacteriana
Antibacterial sole
Semelle antibacterienne



Certificado de origen español
Spanish origin certificate
Certificat d'origine espagnol

CONGRESO



negro



ES Zapato con cierre de elásticos laterales, de piel micro D'COVER PLUS®, forrado en la pala con microfibr técnica D'DRY®, acolchado en el tobillo para evitar rozaduras. Forma recta de puntera redondeada. Contrafuerte de dureza suficiente para sujetar el calcáneo. Plantilla acolchada de microfibr sobre espuma de poliuretano termoconformado con tratamiento antibacterias y carbón activado. Suela de poliuretano antideslizante de doble densidad, bicomponente de poliuretano y TPU combinados para aumentar el coeficiente de eficacia antideslizante del zapato. Fabricado mediante montado y cosido de seguridad para reforzar la unión de la suela al corte del zapato.

Normativa: Certificado CE, norma EN-ISO-20347: 2012 UE 425/2016. Nivel de protección O2+SRA+FO

SRA = antideslizante en baldosa y agua con detergente como lubricante

O2 = parte trasera cerrada, antiestático, absorción de energía en el tacón, suela con resaltes, penetración y absorción de agua.

FO = resistencia a los hidrocarburos de la suela.

EN Shoe with elastic side fastening, micro leather D'COVER PLUS®, inset lined with Technic Microfibre D'DRY® and padded ankle collar to avoid blistering. Straight shape rounded toe. Buttress of sufficient hardness to hold the heel. Microfiber cushioned insole, thermoformed polyurethane foam with antibacterial treatment and activated carbon. Non-skid polyurethane sole dual density, double component polyurethane and TPU combine to increase the antiskid efficiency ratio of the shoe. Manufactured and assembled to reinforce the union of the sole to the upper shoe.

Standards: CE Certificate, Standard EN-ISO-20347:2012 UE 425/2016. Security Level SRA+O2+FO.

SRA = nonslip on tiled surface with detergent and water as a lubricant

O2 = closed back, antistatic, energy absorbing heel, sole with ridges, penetration and water absorption.

FO = oil resistance of the sole.



Diseño registrado / Registered design
Design enregistrée
N° 007342118-0008 (EUIPO)

Tallas / Sizes / Pointures : 35/48



GRUPO
NAVENDI

www.navendi.com

Tel. 948 198 002

629 628 353